

	Standard	Result
Size		See separate table
Thickness		4.5 mm
Wear layer		0.55 mm
Guarantee	Light industrial	10 years*
	Commercial	12 years*
	Domestic	15 years*
Bevelled edge		No
Standards	EN 649	Pass
Classification	EN 685- Light industrial	42: Light industrial general
	EN 685- Commercial	33: Commercial heavy
	EN 685- Domestic	23: Domestic heavy
	ASTM F1700	Class III Type B
Reaction to fire	EN 13501-1	B _{fl} -s1
	EN ISO 9239-1	Pass
	EN ISO 11925-2	Pass
	ASTM E648-06	Class 1
Staining resistance	EN 423	Class 0
	ASTM F925	Pass
Light fastness	EN ISO 105-B02	≥7
	ASTM F1515	<8
Abrasion resistance	EN 660-2	Group T
	ASTM D3884	Pass
Dimensional stability	EN 434	≤ 0.10%
	ASTM F2199	Pass
Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 13 db
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433	≤ 0.1mm
	ASTM F1914	<8%
Castor chair continuous use	EN 425	Pass
Thermal conductivity	ISO 8302	0.0245 m ² K/W
		Suitable for underfloor heating. Max 27°C
Slip resistance	BS 7976	See separate table
	DIN 51130	See separate table
	DIN 51097	See separate table
	EN 13893	DS
	ASTM C1028	ADA Compliant
Light reflectance value	BS 8493:2008+A1:2010	See separate table
Adhesive		Please refer to our installation instructions.
Recycling		Suitable

*Subject to terms

Product	Size (mm)	Slip Resistance				LRV
		BS 7976 (dry)	BS 7976 (wet)	DIN 51130	DIN 51097	
LLP101	1050 X 250	61	33	R10	B	28
LLP102	1050 X 250	61	33	R10	B	14
LLP103	1050 X 250	61	33	R10	B	21
LLP104	1050 X 250	61	33	R10	B	12
LLP105	1050 X 250	61	33	R10	B	29
LLP106	1050 X 250	61	33	R10	B	20
LLP108	1050 X 250	61	33	R10	B	31
LLP109	1050 X 250	61	33	R10	B	21
LLP110	1050 X 250	61	33	R10	B	12
LLP111	1050 X 250	61	33	R10	B	12
LLP112	1050 X 250	61	33	R10	B	16
LLP113	1050 X 250	61	33	R10	B	30
LLP92	1050 X 250	61	33	R10	B	34
LLP93	1050 X 250	59	21	R10	B	7
LLP94	1050 X 250	59	21	R10	B	34
LLP95	1050 X 250	59	21	R10	B	38
LLP96	1050 X 250	59	21	R10	B	11
LLP97	1050 X 250	59	21	R10	B	20
LLP99	1050 X 250	59	21	R10	B	31
LLT200	610 X 500	66	29	R10	A	19
LLT201	610 X 500	66	29	R10	A	32
LLT202	610 X 500	66	29	R10	A	44
LLT203	610 X 500	66	29	R10	A	8
LLT204	610 X 500	66	29	R10	A	18
LLT205	610 X 500	66	29	R10	A	8
LLT206	610 X 500	66	29	R10	A	27
LLT207	610 X 500	66	29	R10	A	13

For more information:

Call: 01386 820104

Email: commercial@karndean.co.uk

Visit: www.karndean.com



Manufactured to:

